

PREVOST

THE ULTIMATE EXPERIENCE

X3-45 VIP ENTERTAINER

- Low center of gravity for excellent driveability
- Abundant under floor storage and custom conversion space
- Exceptional handling with an independent suspension system
- Prevost unique power management system increases battery life and vehicle's power usage
- Integral stainless steel structure for optimal passenger safety
- Prevost Electronic Stability Program provides improved stability in adverse conditions
- Environmentally friendly Volvo D13 engine exceeds EPA emission regulations for clean air and fuel economy

SPECIFICATION HIGHLIGHTS

X3-45 VIP ENTERTAINER

USA

California - Bay Area Tel: (510) 745-7515

California - Southern Tel: 1-800-421-9958

Florida - Jacksonville

Tel: 1-800-874-7740 Florida - Orlando

Tel: 1-407-554-0196

Illinois - Chicago Tel: (847) 778-7475

New Jersey - South Plainfield

Tel: 1-800-223-0830

Tennessee - Nashville Tel: 1-877-299-8881

Texas - Fort Worth

Tel: 1-866-773-8678 Texas - Houston

Tel: 1-877-602-0273

Prevost USA Parts Customer Service

Tel Eastern Region: 1-877-279-1224 Tel Central Region: 1-877-279-1245 Tel Western Region: 1-877-279-1219

Canada

Alberta - Calgary Tel: 1-833-644-6294

Alberta - Ft McMurray

Tel: 1-780-713-0274

British Columbia - Richmond

Tel: 1-604-940-3306

Ontario - Mississauga

Tel: 1-905-738-0881

Quebec - Lévis

Tel: 1-866-870-2046

Quebec - Montreal

Tel: 1-514-882-8973

Prevost Canada Parts Customer Service

Tel: 1-800-463-8876

prevostcar.com











These specifications are based on the latest product information available at time of printing (05/19) and are subject to change. Contact your Prevost Sales Manager for full details on standard features, packages and options available on the latest model.

CENEDAL

GENERAL	
Length, Overall (ft)	45
Wheelbase (in)	334.5
Width, Overall (in)	102
Height, Overall (in)	143.625
Floor-to-ceiling Height (in)	91.5
Cabin Floor Height (in)	49
Underfloor Storage (w/ driver A/0	(cu. ft.) 433
Underfloor Compartment Doors	
Entrance Door Width (in)	30.25
Step Height (in)	7" inside entrance steps
9	3/8" for the first step from
	the ground when kneeled
Ground Clearance (in)	11
Overhang (incl. bumper) - Front (
Overhang (incl. bumper) - Rear (in	
Turning Radius (ft)	43.3
Body Construction (structure)	Integral (Stainless/Rust
	Protected Mild Steel)
Body Construction	Luggage doors:
	Ribbed stainless steel
Body Construction (Sub-Frame)	Low-Alloy/
	High Tensile Steel
State-of-the-art Soundproofing	Standard
Fuel Tank (US gallons)	203
Fuel Filler Necks on Both Sides	Standard
Diesel Exhaust Fluid (DEF) Filler o	
Gross Vehicle Weight Rating (lb/k	
Axle Design Load Capacity - Front	
Axle Design Load Capacity - Drive	
Axle Design Load Capacity - Tag (Wet Weight, w/ Driver A/C (lb/kg)	lb/kg) 14,000/6,350 30,540/13,853
Wet Weight, w/ Full A/C (lb/kg)	30,850/14,023
Driver-only A/C	Standard
Full A/C	Optional
A/C Condenser w/ Copper Fins	Standard with full A/C
A/C Refrigerant	134A
Cooling Capacity/Full A/C	108,000 btu/hr or 9 tons
Two-Year Warranty	Standard
Five-Year Extended Warranty	Staridard
(engine & transmission)	Standard
TIRES AND WHEELS	
Michelin 315/80R22.5 (drive axle)	
Michelin 365/70R22.5 (front and	
Aluminum Wheels 22.5 x 9 in. (dr	ive axle) Standard
Aluminum Wheels 22.5 x 10.5 in.	
(front and tag axles)	Standard
Dura-Bright Coating (aluminum v	
Michelin 455/55R22.5 Super Sing	le Tires

w/14" Wheels (drive axle)

POWERTRAIN

EPA Compliant Volvo D13 Engine 500HP	
w/ Diesel Particulate Filter (DPF) and	
Selective Catalytic Reduction (SCR)	Standard
Engine Torque Rating (ftlb.)	1850
Allison 6 speed Automatic Transmission	Standard
Allison Hydraulic Transmission Retarder	Optional
Cruise Control	Standard
Engine Brake (on all cylinders)	Optional
Pneumatic Drive Belts Tensioners	Standard
Turbo-boost Gauge	Standard
Electric Air Intake Preheater	Standard
Prevost Exclusive - Electric engine	
Cooling Package	Standard
Coolant System w/ Recovery Tank	Standard
Engine Coolant Filter	Standard
Two-step Dual Filter w/ Water Separator	Standard
Prevost Liaison – 1 Year Coverage	Standard
Engine Maintenance Software w/ Laptop	Optional
Driver Electronic Message Center Display	Standard
Fuel Pro 382 Fuel Filter	Optional

BRAKES

All-disc Brakes w/ ABS	Standard
Front Wheels Brake Boosters	Type 27
Driver Wheels Brake Boosters	Type 24-24
Tag Wheels Brake Boosters	Type 20
Parking Brake Booster on Tag Wheels	Standard

STEERING AND SUSPENSION

Tilt and Telescopic Steering Wheel	Standard
Bosch Constant Assistance Power Steering System	Standard
Bosch Variable Assistance Power Steering System	Optiona
Independent Suspension System	Standard
Front and Drive Axle Sway Bars	Standard
Integrated Pneumatic Level-	
Low Leveling System	Standard
Liftable Tag Axle	Standard

ELECTRICAL SYSTEM

Optional

Fully Multiplexed Electrical System	Standard
12-volt Exterior Lighting	Standard
24-volt Main System	Standard
Additional Alternator Configurations	
For Conversion	Optiona
4 AGM Batteries	Standard
Energy Management System	Standard

INNOVATIVE SAFETY FEATURES

Prevost Electronic Stability Program	Standard
Prevost Aware - Adaptive Cruise	
and Collision Warning System	Optiona
Automatic Fire Suppression System	Standard
Tire Pressure Monitoring System	Standard
Xenon Headlights	Standard

FACTORY-INSTALLED EQUIPMENT

Patented Prevost BEAM Frame Reinforcement	
For Factory Installed Slide-Outs	Standard
Factory Slide-Outs (electrical motors & pneum	atic
seals w/ aluminum frames)	Optional
Front Slide Driver's Side	
(interior dimensions) 1-	40" x 24" x 78'
Choice of Side Window Arrangement &	
Type Fixed, Electrical Awning or Sliding	Optional
LED Fog Lights	Standard
Driver's Window Blind	Optiona
Left/Right Windshield Manual Blind	Standard
Electric Windshield Blinds LH and RH	Optional
Ramco Remote Heated Rearview Mirrors	
w/ Separate Convex Top (painted in black)	Standard
w/ Separate Convex Top (chromed)	Optional
Signal Mirrors w/ LED Light	Optiona
Keyless Keypad w/ Multi-Code Capability	Standard
Central Electrical Door Locking System	Standard
Remote and Keyless Locking (entrance door)	Standard
Remote and Keyless Locking (compartment door	r) Standard
Trailer Hitch Package (20,000 lb)	Standard
Trailer Air Brake Connection	Optiona
Low Fuel Warning Light	Standard
Courtesy Lights Blinker Switch	Standard
Engine and Compartment Lighting	Standard
ISRI 6832 3 pt Seat Belt Air Ride Seat	Optional
ISRI 6832 Climate Control	
(heater and air circulation)	Optiona
Exterior Graphic Design Assistance	Optiona
Factory Exterior Paint w/ Special Effect	Optiona
Back-up Sound Alarm	Standard
Headlamp Cleaning System	Standard
Emergency Escape Hatches	Optiona