

PREVOST

X3()

.....

**X3-45 VIP** | Specification

Max Indo

A sta

100

### General

Length, Overall (ft)	45
Wheelbase (in)	334.5
Width, Overall (in)	102
Height, Overall (in)	143.625
Floor-to-ceiling Height (in)	91.5
Cabin Floor Height (in)	49
Underfloor Storage (w/ driver A/C) (cu. ft.)	433
Underfloor Compartment Doors Width (in)	70.6
Entrance Door Width (in)	30.25
Step Height (in)	7", inside entrance steps
	9 3/8" for the first step from the ground when kneeled
Ground Clearance (in)	11
Overhang (incl. bumper) - Front (in)	72.25
Overhang (incl. bumper) - Rear (in)	86.6
Turning Radius (ft)	43.3
Body Construction (structure)	Integral (Stainless/Rust Protected Mild Steel)
Body Construction	Luggage doors and side panels: Ribbed stainless steel
Body Construction (Sub-Frame)	Low-Alloy/High Tensile Steel
State-of-the-art Soundproofing	Standard
Fuel Tank (US gallons)	203
Fuel Filler Necks on Both Sides	Standard
Diesel Exhaust Fluid (DEF) Filler on Driver's Side	Standard
Gross Vehicle Weight Rating (lb/kg)	55,500/25,227
Axle Design Load Capacity - Front (lb/kg)	19,000/8,648
Axle Design Load Capacity - Drive (lb/kg)	22,500/10,205
Axle Design Load Capacity - Tag (lb/kg)	14,000/6,350
Wet Weight, w/ Driver A/C (lb/kg)	30,540/13,853
Wet Weight, w/ Full A/C (lb/kg)	30,850/14,023
Driver-only A/C	Standard
Full A/C	Optional
A/C Condenser w/ Copper Fins	Standard with full A/C
A/C Refrigerant	134A
Cooling Capacity/Full A/C	108,000 btu/hr or 9 tons
Two-Year Warranty	Standard
Five-Year Extended Warranty (engine & transmission)	Standard

## Tires and wheels

Michelin 315/80R22.5 (drive axle)	Standard
Michelin 365/70R22.5 (front and tag axles)	Standard
Aluminum Wheels 22.5 x 9 in. (drive axle)	Standard
Aluminum Wheels 22.5 x 10.5 in. (front and tag axles)	Standard
Dura-Bright Coating (aluminum wheels)	Optional
Michelin 455/55R22.5 super single tires w/14" wheels (drive axle)	Optional

### Powertrain

EPA Compliant Volvo D13 Engine 500HP w/ Diesel Particulate Filter (DPF)	
and Selective Catalytic Converter (SCR)	Standard
Engine Torque Rating (ftlb.)	1850
Allison 6 speed Automatic Transmission	Standard
Allison Hydraulic Transmission Retarder	Optional
Cruise Control	Standard
Engine Brake (on all cylinders)	Optional
Pneumatic Drive Belts Tensioners	Standard
Turbo-boost Gauge	Standard
Electric Air Intake Preheater	Standard
Prevost Exclusive - Electric engine Cooling Package	Standard
Coolant System w/ Recovery Tank	Standard
Engine Coolant Filter	Standard
Two-step Dual Filter w/ Water Separator	Standard
Prevost Liaison – 1 Year Coverage	Standard
Engine Maintenance Software w/ Laptop	Optional
Driver Electronic Message Center Display	Standard
Fuel Pro 386 Fuel Filter	Optional

### Brakes

All-disc Brakes w/ ABS	Standard
Front Wheels Brake Boosters	Type 27
Driver Wheels Brake Boosters	Type 24-24
Tag Wheels Brake Boosters	Type 20
Parking Brake Booster on Tag Wheels	Standard

# Steering and suspension

Tilt and Telescopic Steering Wheel	Standard
Bosch Constant Assistance Power Steering System	Standard
Independent Suspension System	Standard
Front and Drive Axle Sway Bars	Standard
Integrated Pneumatic Level-Low Leveling System	Standard
Liftable Tag Axle	Standard

## Electrical system

Fully Multiplexed Electrical System	Standard
12-volt Exterior Lighting	Standard
24-volt Main System	Standard
Additional Alternator Configurations for Conversion	Optional
4 AGM Batteries	Standard
Energy Management System	Standard

## Innovative safety features

Prevost Electronic Stability Program	Standard
Prevost Aware - Adaptive Cruise and Collision Warning System	Optional
Automatic Fire Suppression System	Standard
Tire Pressure Monitoring System	Standard
Xenon Headlights	Standard

## Factory-installed equipment

actory instance equipment	
Patented Prevost BEAM Frame Reinforcement for Factory Installed Slide-Outs	Standard
Factory Slide-Outs (electrical motors & pneumatic seals w/ aluminum frames)	Optional
(1, 2, 3 or 4 slide-outs available)	
Front Slide Driver's Side (interior dimensions)	170" x 30" x 78"
Rear slide driver's side (interior dimensions)	86" x 24" x 65"
Rear super slide driver's side (interior dimensions)	128" x 24" x 65"
Choice of Side Window Arrangement & Type Fixed, Electrical Awning or Sliding	Optional
LED Fog Lights Standard	
Driver's Window Blind Optional	
Left/Right Windshield Manual Blind Standard	
Electric Windshield Blinds LH and RH Optional	
Ramco Remote Heated Rearview Mirrors	
w/ Separate Convex Top (painted in black)	Standard
w/ Separate Convex Top (chromed)	Optional
Signal Mirrors w/ LED Light	Optional
Keyless Keypad w/ Multi-Code Capability	Standard
Central Electrical Door Locking System	Standard
Remote and Keyless Locking (entrance door)	Standard
Remote and Keyless Locking (compartment door)	Standard
Trailer Hitch Package (20,000 lb)	Standard
Trailer Air Brake Connection	Optional
Low Fuel Warning Light	Standard
Courtesy Lights Blinker Switch	Standard
Engine and Compartment Lighting	Standard
ISRI 6832 3 pt Seat Belt Air Ride Seat	Optional
ISRI 6832 Climate Control (heater and air circulation)	Optional
Exterior Graphic Design Assistance	Optional
Factory Exterior Paint w/ Special Effect	Optional
Back-up Sound Alarm	Standard
Headlamp Cleaning System	Standard
Emergency Escape Hatches	Optional

in f 9 0 @PrevostCoach